


INOX Comfort

Use:



DHW



Advantages:

- Made with high-quality **Duplex 2202 stainless steel**
- Manufactured using **inerting and passivation** processes, helping to preserve the properties of the stainless steel and reducing the risk of surface oxidation.
- **No magnesium anode**, reducing maintenance.
- Brackets for **wall and floor installation included**.
- **Analogue thermostat**, can be set from 30 to 75°C.
- **1500 W to 3000 W titanium** heating element.
- **Thermometer** to read hot water delivery temperature.
- 160 mm inspection flange on 300 l-litre models.
- **7-year warranty**, subject to the manufacturer's terms and conditions.

Models:

- Wall 50 L to 150 L and floor 150 L to 300 L.

Accessories:

- 2050037: 1 1/4" 1500 W titanium heating element
- 2042842: 1 1/4" 1500 W titanium heating element with IP65
- Thermostat 2042843: 1 1/4" 3000 W titanium heating element with IP65
- Thermostat 2050244: Adjustable analogue thermostat

Technical characteristics:


Model	TERMO 50 COMFORT CORE M	TERMO 80 COMFORT CORE M	TERMO 100 COMFORT CORE M	TERMO 120 COMFORT CORE M	TERMO 150 COMFORT CORE M	TERMO 150 COMFORT CORE	TERMO 200 COMFORT CORE	TERMO 300 COMFORT CORE
Code	2052689	2052690	2052691	2052692	2052693	2052694	2052695	2052696
Installation*	Vertical wall mounted					Vertical floor mounted		
Capacity [l]	47	76	96	116	150	150	190	280
Heating element	1500 W titanium (2050037)					Titanium 1500 W (2042842)	3000 W titanium (2042843)	
Controller	Adjustable analogue thermostat (2050244)					Thermostat included in the heating element		
Maximum pressure	8 bar							
Outer finish	Grey lacquered galvanised steel							
Insulation	Injected rigid polyurethane. Thickness: 30 mm. Density: 42kg/m3							
Tank protection	Not necessary							
Diameter [mm]	540	540	540	540	540	540	540	540
Height [mm]	485	655	745	855	1050	1014	1234	1757
Weight when empty [kg]	17	22	26	29	31	30	38	49
Boiler material	Duplex 2202 stainless steel							

*Can be fitted inside the home.

Wall version (100-150)



- *Drain (Wall 50-150L): consult manual



Dimensions [mm]	TERMO 50 COMFORT CORE M	TERMO 80 COMFORT CORE M	TERMO 100 COMFORT CORE M	TERMO 120 COMFORT CORE M	TERMO 150 COMFORT CORE M	TERMO 150 COMFORT CORE	TERMO 200 COMFORT CORE	TERMO 300 COMFORT CORE
L	492	661	752	862	1052	1014	1234	1757
L1	196	365	456	566	756	292	402	655
L2	-	-	-	-	-	-	-	655