

SLIM Inercia Comfort

COMFORT RANGE



Use:




Heating and refrigeration



Heat pump



Boiler



Advantages:

- Boiler made of stainless steel
- Especially designed for heat pumps.
- Can be installed both inside and outside the home.
Manufactured using **inerting and passivation** processes, helping to preserve the properties of the stainless steel and reducing the risk of surface oxidation.
- Brackets for wall and floor installation included.
- 5-year warranty, subject to the manufacturer's terms and conditions.

Models:

- 30 L, 40 L, 50 L and 60 L.

Accessories:

- SLIM pair vent (Ceiling installation)



Technical characteristics:

Model	SLIM 30 COMFORT	SLIM 40 COMFORT	SLIM 50 COMFORT	SLIM 60 COMFORT
Code	2052362	2052360	2052363	2052364
Capacity [l]	30	40	50	60
Maximum pressure	6 bar			
Operating range [°C]	-10 to 100			
Outer finish	Grey lacquered galvanised steel			
Insulation	Injected rigid polyurethane. Density: 42kg/m³			
Insulation thickness [mm]	20			
Diameter [mm]	310	310	310	310
Height [mm]	674	849	1029	1209
Weight when empty [kg]	13.50	15	16.50	18
Boiler material	Stainless steel			

COMFORT RANGE

Technical drawing of a 1000L buffer tank, showing front, top, and side views with dimensions in mm.

Dimensions:

- Top View:**
 - Overall width: 334
 - Overall height: 326
 - Inner diameter: $\varnothing 310$
- Front View:**
 - Overall width: 334
 - Overall height: 165
 - Mounting bracket width: 165
- Side View:**
 - Overall height: A
 - Top section height: C
 - Bottom section height: F
 - Section height: D

Legend:

1. Buffer tank connections [1 1/4" F]
2. Purge / safety valve / probes [1/2" F]

Dimensions [mm]	SLIM 30 COMFORT	SLIM 40 COMFORT	SLIM 50 COMFORT	SLIM 60 COMFORT
A	674	849	1029	1209
B	348	435	525	615
C	292	467	647	827
D	146	234	324	414
E	320	440	620	779
F	199	199	199	199
G	188	215	215	226